



SOLDRON[®]

w w w . s o l d r o n . c o m



SI25A

SI1530A

SI35A

SI50A

SI75A

SI100A

SIIST100

SIVT

VAFG15-30



BOMBAY INSULATED CABLES & WIRES CO.

Since 1953

INDEX

SR. NO.	CATEGORY	PAGES
1.	SOLDERING IRON	1 - 6
2.	SOLDRON NEW PRODUCTS	7 - 10
3.	SOLDERING STATION	11 - 16
4.	SOLDERING BIT	17 - 19
5.	DE-SOLDERING PUMP	20
6.	SOLDERING ELEMENTS	21 - 22
7.	DC POWER SUPPLY	23 - 24
8.	MOBILE REPAIRING TOOLS	25
9.	DE-SOLDERING KIT	26
10.	SOLDERING ACCESSORIES	27-28



SOLDERING IRONS

A soldering iron is a hand tool used in soldering. It supplies heat to melt solder so that it can flow into the joint between two workpieces.

A soldering iron is composed of a heated metal tip (the bit) and an insulated handle. Heating is often achieved electrically, by passing an electric current (supplied through an electrical cord or battery cables) through a resistive heating element. Cordless irons can be heated by combustion of gas stored in a small tank, often using a catalytic heater rather than a flame. Simple irons, less commonly used today than in the past, were simply a large copper bit on a handle, heated in a flame.

SOLDRON 15 WATTS/230 VOLTS SOLDERING IRON

SI15A



Specifications

Wattage	: 15W
Input Voltage	: 230VAC
Temperature	: 360°C max. ($\pm 10^\circ\text{C}$)
Wire	: 3 core (1.4 mtrs length)
Bit Supplied	: BN15S3

This model is ideal for hobbyists. Can be used for any applications with a low-heat soldering requirement.

SOLDRON 25 W/230 V SOLDERING IRON LIMITED EDITION

SI25ALE



Specifications

Wattage	: 25W
Input Voltage	: 230VAC
Temperature	: 380°C max. ($\pm 10^\circ\text{C}$)
Wire	: 3 core (1.4 mtrs length)
Bit Supplied	: CB25S3

The culmination of 30+ years of R&D, our flagship 25 Watt MCH iron is the pinnacle of all purpose soldering applications, design and technology, the Limited Edition is everything an engineer ever dreamed of.

SOLDRON 25 WATTS / 230 VOLTS SOLDERING IRON

SI25A



Specifications

Wattage	: 25W
Input Voltage	: 230VAC
Temperature	: 380°C max. ($\pm 10^\circ\text{C}$)
Wire	: 3 core (1.4 mtrs length)
Bit Supplied	: BN25S3

The 25 Watt SI25A has been through many iterations since our conception in 1983 and continues to be our best seller and most loved product till date.

SOLDRON 25W LOW VOLTAGE 12 VOLTS AC/DC

SI2512L



Specifications

Input Voltage	: 12V AC or DC
Current Ratings	: 2.1 Amps
Wire	: 2 core (with clip at the end)
Temperature	: 350 °C (±10°C)
Bit Supplied	: BN25S3

This model is ideal for hobbyists. Can be used for any applications with a low-heat soldering requirement.

SOLDRON 25W LOW VOLTAGE 24 VOLTS AC/DC

SI2524L



Specifications

Input Voltage	: 24V AC or DC
Current Ratings	: 1 Amps
Temperature	: 350 °C (±10°C)
Wire	: 2 core (with lugs at the end)
Bit Supplied	: BN25S3

This model is ideal for hobbyists. Can be used for any applications with a low-heat soldering requirement.

SOLDRON GUN TYPE DUAL WATTAGE SOLDERING IRON

SI2550A



Specifications

Wattage	: 25W - 50W
Input Voltage	: 230V
Temperature	: 350 °C max. (± 10°C)
Current Ratings	: 2.1 Amps
Wire	: 3 core (1.4mtrs length)

Temperatures: 350°C or 450°C Ideal for service engineers as they can boost temperature instantly by pressing trigger for that occasional heavy soldering. (Trigger may be pressed maximum for 1 minute.) Avoids carrying two irons.

SOLDRON 35WATTS/230VOLTS SOLDERING IRON

SI35A



Specifications

Wattage	: 35W
Input Voltage	: 230VAC
Temperature	: 420°C max. (± 10°C)
Wire	: 3 core (1.4 mtrs length)
Bit Supplied	: BN15S3

Maximum Temperature: 420°C For medium heavy power electronic circuits. Rugged with long life tip as standard.

SOLDRON 50WATTS/230VOLTS SOLDERING IRON

SI50A



Specifications

Wattage	: 50 Watts
Input Voltage	: 230 Volts
Temperature	: 460°C (± 10°C)
Wire	: 3 core
Bit Supplied	: BN50S5

The big brother of our flagship 25W Iron, this 50 Watt variant suits jobs that require higher temperatures.

SOLDRON 75WATTS/230VOLTS SOLDERING IRON

SI75A



Specifications

Wattage	: 75W
Input Voltage	: 230Vac
Temperature	: 480°C max. (± 10°C)
Wire	: 3core /1.4mtrs length
Bit supplied	: BN75S6

Maximum Temperature: 500°C Ideal for the electrical and automotive industries. Comes with comfortable rubber coated handle.

SOLDRON 100 WATTS/230 VOLTS SOLDERING IRON

SI100A



Specifications

Wattage	: 100W
Input Voltage	: 230Vac
Temperature	: 550°C max. (± 10°C)
Wire	: 3 core (1.4 mtrs length)
Bit Supplied	: BN100S8

The Most Efficient and Economic 100 Watt Soldering Iron, Designed and Manufactured In-House by Soldron In India!

SOLDRON 100 WATTS/230 VOLTS SOLDERING IRON

**SPARE REPLACEMENT SOLDERING IRON FOR
SOLDRON 936/878D/740 STATIONS.**

SI878A



Specifications

Wattage	: 60Watts
Sleep Sensor	: No
ESD Safe	: Yes
Bit Supplied	: SBN1

Spare replacement soldering Iron accessory for Soldron 936/ 878D/ 740 Stations

SPARE REPLACEMENT SOLDERING IRON FOR SOLDRON 938 STATION

SI938A



Specifications

Wattage	: 60Watts
Sleep Sensor	: Yes
ESD Safe	: Yes
Bit Supplied	: SBN1

Spare replacement soldering Iron accessory for Soldron 938 Station

SOLDRON PROFESSIONAL DIGITAL TEMPERATURE ADJUSTABLE SOLDERING IRON(SOLDERMALL EXCLUSIVE)

SID60A



Specifications

Input	: 230VAc/50Hz
Watts	: 60W
Temperature	: 180°C - 500°C
LCD display	: Yes
Temperature setting	: Push buttons
Heater Type	: Ceramic Solid State

Using the latest MCH heater technology developed in-house by Soldron which provides lightning fast heating and excellent temperature stability with negligible loss of heat which saves time, energy and allows the user to work continuously for long hours without being fatigued.

SOLDRON VARITEMP VARIABLE WATTAGE SOLDERING IRON

SIVT



Specifications

Wattage	: 15W-30W
Input Voltage	: 230VAC
Temperature	: 280°C to 450°C
Wire	: 3core (1.4mtrs length)
Bit Supplied	: BP1530N3

Efficiency and Versatility to switch wattages at mid-application at the twist of a knob without a bulky station!

SPARE REPLACEMENT 500W HOT AIR BLOWER FOR SOLDRON 878D/858D/740 STATIONS

BL500A



Specifications

Wattage	: 500W
Temperature	: 200-480 °C
Cut-off Sensor	: Magnetic
Blower	: 12VDC
Cable Length	: 1.2mtrs
Temperature Sensor	: Thermocouple

Spare Replacement 500W Hot Air Blower for Soldron 878D/858D/740/8858 Stations

SOLDRON VARIABLE WATTAGE AUTO FEEDER GUN

VAFG 15-30



- Come with an arc shaped solder feeding trigger, easy to press, improving work efficiency
- Power is 15-30W, possess low power consumption, energy-saving, economical and applicable
- Equipped with detachable solder coil rack, easy to disassemble and install solder wire
- Brass electric soldering iron, secondary plating on the surface, fast heating, safe and secure

SPECIFICATIONS OF VAFG 15-30W

Model	: SOLDRON VAFG15-30
Power	: 15-30W
Temperature	: 250°C - 550 °C
Input Voltage	: 230VAC
Frequency	: 50/60Hz
Operation Solder wire	: 0.6mm - 1.8mm

SOLDRON T210 SOLDERING STATION

T210



Highly ergonomic design for comfortable use.

- 3 temperature memory preset buttons, for instant change of configuration
- The T210 has a Super-Fast “3 Second” Warm Up (500°C/932°F)
- Maintains Temperature Stability at $\pm 1.8^{\circ}\text{F}/1.0^{\circ}\text{C}$.
- ESD Safe, Lead-Free, 3 Programmable Temperature Pre-set Buttons, Hibernation (Sleep) Function (3 Second Wake Up from Hibernation).
- Precision and durable iron head, easily changeable integrated element / bit

SPECIFICATIONS OF T210 STATION

Model	: SOLDRON T210
Input Voltage	: 220V AC/110V AC
Output Power	: 85W
Output Temperature	: 200°C ~ 500°C

BOX INCLUDES

1 X SOLDRON T210 station
1 X T210 Iron
2 X T210 Bit
1 X Power cord

SOLDRON PLUG VARIABLE WATTAGE SOLDERING IRON

SI15-30A



1. Fitted with a premium-grade, long-life ceramic-coated bit (X10 the life of a standard nickel-plated bit.).
2. Reduced length of iron for precision work.
3. Best-quality (FR-grade and burn-resistant) 3-core copper wire.
4. Ergonomically shaped, tri-grip handle with ridges for comfortable, slip-free use.
5. Solid-state printed ceramic heater; semi-thermostatic
Extremely long life and rapid heating

SPECIFICATIONS OF PLUG VARIABLE WATTAGE SOLDERING IRON

Model No	: Soldron [®] SI15-30A
Input Voltage	: 220V AC
Output Temperature	: 250°C - 480°C
Output Power	: 15-30 W
Wire Length	: 3 core mains cord 1.2mtrs
Bit Supplied	: CB15-30S3 / CB15-30N3

MICROSCOPE FOR PCB MOTHERBOARD INSPECTION.

D75T MICROSCOPE



SPECIFICATIONS OF MICROSCOPE FOR PCB MOTHERBOARD INSPECTION.

Product Name	: Industrial grade trinocular stereo microscope
Product Model	: D75T-PRO
Product Size	: 195*253*225mm
Magnification	: Standard 0.7-4.5X(Optional 2.1X-180X)
Eyepiece	: 0.5X CTV HD electron microscope
Objective Len	: 0.7X-50X
Eyepiece	: WF10X22 High Eyepiece
Observation Head	: Binocular observation head 45°tilt, eyepiece pupil spacing adjustment range 54-76mm; Binocular visual acuity adjustable
Working distance	: The effective distance is 100mm, and the purchase of an auxiliary objective lens can be extended to 30-287mm
Focusing bracket	: Adjustable elasticity of focusing handwheel, lifting range 50mm
Base Size	: 195*256*20mm
LED light source	: High brightness cold white light source, can be adjusted freely
Applicable Fields	: Teaching Demonstafion, PCB electronics signal mobile phone processing and repair Component Assembly, electronic component detection



SOLDERING STATIONS

A soldering station is a multipurpose power soldering device designed for electronic components soldering. This type of equipment is mostly used in electronics and electrical engineering. Soldering station consists of one or more soldering tools connected to the main unit, which includes the controls (temperature adjustment), means of indication, and may be equipped with an electric transformer. Soldering stations may include some accessories – holders and stands, soldering tip cleaners, etc.

Soldering stations are widely used in electronics repair workshops, electronic laboratories, in industry. Sometimes simple soldering stations are used for household applications and for hobbies.

SOLDRON VARIABLE WATTAGE MICRO-SOLDERING STATION

MSVW

Ideal for precision small jobs like SMT and micro-electronics. Element shaft is only 2.5mm thick with an isolated element! It can be set to high, medium or low with a continuously variable knob, and comes with a sponge tray with a sponge and a placing stand as standard. Comes standard with an aluminium coated long life tip. Very popular amongst jewellery manufacturers for trimming/ sculpture of wax casting.

Specifications

Input Voltage	: 230V AC
Power	: 6-12 Watts (Variable)
Control	: Analog Variable
Temperature	: 200°C to 350°C
Cable Length	: Main Cord : 1,25 mtrs Iron Cord : 1.25mtrs
Power Supply	: Transformer based



Package Contains

- 1) 1 X Station.
- 2) 1 X Soldering Iron (with bit).
- 3) 1 X Iron Stand (spring incorporatd on body).
- 4) 1 X Sponge.

SOLDRON PORTABLE SMPS VARIABLE WATTAGE MICRO SOLDERING STATION

SMPS

Our most versatile and advanced micro-sized soldering station, this unit is nothing short of a technological marvel as it provides the highest level of safety and maneuverability in a micro sized form factor.

Absolutely ESD safe and ideal for SMD/SMT work and rework.

Specifications

Input Voltage	: 90 to 250VAC / 50Hz
Power	: 4 - 18Watts
Temperature	: 180°C to 380°C
Safety	: Inbuilt Smart Current, Voltage, Temperature Monitoring IC
Tip Size	: 0,5 mm
Heating Element	: Ceramic type
Station case	: ABS
Indicator	: Yes
Wire length	: 3 core mains cord - 1.2mtrs / 2core iron wire - 1.2mtrs



Package Contains

- 1) 1 X Station.
- 2) 1 X Soldering Iron with bit.
- 3) 1 X Stand with Spring & Sponge.

SOLDRON 8858 PORTABLE HOT AIR BLOWER

8858

An innovative first-of-its-kind product to be exclusively brought to you in India by Soldron and Soldermall.

This is the newest, most efficient portable solution for Hot-Air Soldering and Rework Applications.

The best and most affordable gear for Mobile Repairers and PCB work on the it. Small enough to fit into even the tightest of work spaces.

Specifications

Input Voltage	: 230Volts AC
Power	: 350Watts output max.
Temperature	: 100°C to 480°C Digitally controlled
Fan Control	: 1 to 10 set points Digitally controlled (1 to 4 from 100°C to 299°C) (5 to 10 from 300°C to 480°C)
Display	: 7 segment 3 digit Red LED display



Package Contains

- 1) 1X 8858 Control unit.
- 2) 1X (BL500A) Hot Air Blower.
- 3) 1X Cradle/Stand.
- 4) 1X Set of 3 nozzles.
- 5) 1X Power cord.

SOLDRON 740 3-IN-1 HOT AIR AND SOLDERING STATION

SL740

One of Soldron's Hottest Selling Stations! Designed and built keeping requirements of engineers and technicians in mind, who may have limited work space for a wide spectrum of the most useful soldering solution features available at their fingertips.

Specifications

Input	: 230VAc
Power	: 600W
Hot Air Bower Power	: 500W
Blower Temp.	: 200°C to 450°C
Soldering Iron	: 60W
Iron Temp.	: 200°C to 480°C
DC power supply	: 15V/2Amps max., with 5V USB out.
Controller type	: Micro Controller based
Temp Set Run mode	: Printed (with LED indicator)
Station Body	: Mettalic body with powder coating



Package Contains

- 1) 1 X Hot air blower
- 2) 1 X soldering iron
- 3) Built in SMPS with USB port with output voltage of 5V/1Amps (In test mode max 25V)
- 4) Ammeter with ports for attaching testing probes
- 5) Auto-pause for blower when placed in attached cradle

SOLDRON 936 TEMPERATURE CONTROLLED ANALOG SOLDERING STATION

SL936

Soldron entry level Soldering Station makes do without an LCD display and other fancy bells and whistles. This might be a simple iron but still comes with all the important basics, such as ESD safety and advanced transformer based power to the element. You can tell that the iron is running by the LED light blinking.

Specifications

Input	: 230V AC
Power	: 60Watts
Type	: Analog Control
Source Cable Length	: 1.35 mtrs.
Iron Cable Length	: 1.35 mtrs.
Temperature Range	: 200°C - 480°C
Sleep Mode	: No



Package Contains

- 1) 1 X Station.
- 2) 1 X Soldering Iron (with Bit).
- 3) 1 X Stand with Sponge.

SOLDRON 938 TEMPERATURE CONTROLLED DIGITAL SOLDERING STATION WITH SLEEP MODE

SL938

Currently the only Soldron station with sleep mode. With this station you can save electricity and the cost of buying new bits, thanks to the sleep mode system built into it.

Specifications

Input	: 230V AC
Power Consumption	: 60Watts
Type	: Digital Control
Source Cable Length	: 1.35 mtrs.
Iron Cable Length	: 1.35 mtrs.
Temperature Range	: 200°C - 480°C
Sleep Mode	: Yes (auto mode 15mins if iron kept idle/untouched)



Package Contains

- 1) 1 X Station.
- 2) 1 X Soldering Iron with bit.
- 3) 1 X Stand with Sponge

SOLDRON 858D HOT AIR SOLDERING STATION

858D

This is the most economic and efficient solution for ESD Safe Hot-Air Soldering Station.

The best station for Mobile Repairers and PCB work.

Specifications

Watts	: 500 W
Temperature	: 100°C - 450°C max. (± 10°C)
Input	: 230VAC
Fan speed	: 1-8 Set point

Package Contains

- 1) 1 X Station
- 2) 1 X (BL500A) Hot Air Blower.
- 3) 1 X Cradle/Stand.
- 4) 3 X nozzles Set
- 5) 1 X Power cord.



PORTABLE DUAL HOT AIR SOLDERING STATION

8898

Hot air heater and soldering iron 2in1 rework soldering station.

Dual LCD digital displays to show precision temperature. Extremely low noise and space saving design. Intelligence self-detection function features safe personal operation. Automatic cooling function for effectively prolonging the heater's life and protecting the hot air heater.

Specifications

Hot Air Blower

Working Voltage	: AC220-240V OR AC100-130V
Frequency	: 50Hz/60Hz
Output Power	: 750W
Temperature Range	: 100°C~480°C
Blower speed	: 1 To 10 Digitally Controlled
Temperature Stability	: ±2°C
Air Flow	: 150L/min (max)

Soldering Iron

Working Voltage	: AC220-240V OR AC100-130V
Output Power	: 80W
Frequency	: 50Hz/60Hz
Temperature Range	: 180°C-500°C
Temperature Stability	: ±1°C



SOLDRON 878D 2-IN-1 HOT AIR AND SOLDERING STATION

878D

The ultimate combo of Hot air and Soldering Iron, the 878D is the best combo-station that an advanced multi-engineer can buy. The hot air blower is its own separate unit, that can easily be replaced instead of changing the whole unit like pipe based stations, where the blower unit is inside the station.

Specifications

Watts	: 600 watts all combined
Iron Temperature	: 60W 480°C max. ($\pm 10^\circ\text{C}$)
Blower Temperature	: 550W max. 450°C max. ($\pm 10^\circ\text{C}$)
Input	: 230V/AC
Station Body	: Aluminium body with powder coated
Controller	: Micro Controller based with 7 segment display



Package Contains

- 1) 1 X Station.
- 2) 1 X Soldering Iron (with bit).
- 3) 1 X Blower
- 3) 1 X Iron Stand with sponge.
- 4) 3 X Nozzle.
- 5) 1 X Power Cord and Cradle

SOLDRON IST-100 EDDY CURRENT SOLDERING STATION

IST 100

The IST-100 is the First-Of-It's-Kind in India, SolderMall's ultimate station for extremely high precision soldering using Eddy Current Technology.

Specifications

Input	: 230V AC
Power Consumption	: 100W
Type	: Digital Control
Source Cable Length	: 1.35 mtrs.
Iron Cable Length	: 1.35 mtrs.
Temperature Range	: 200 deg.C - 480 deg.C
Sleep Mode	: Yes (auto mode 15mins if iron kept idle/untouched)



Package Contains

- 1) 1 X Station
- 2) 1 X Soldering Iron with bit
- 3) 1 X Iron Stand with Sponge
- 4) 1 X Power Cord



SOLDERING BITS

A soldering Bit is a part of soldering iron which normally used for applying heat to two or more adjoining metal parts such that solder may melt and flow between those parts, binding them securely, conductively and hermetically.

Spade



Knife Tip



Soldering Bit Types

Needle



Bent Tip




Chisel



NICKEL PLATED SPADE BIT


BN25S3



Standard bit that comes with Soldron 25W Soldering Iron

NICKEL PLATED NEEDLE BIT

BN25N3



To be used with the Soldron 25 W Soldering Iron

BLACK CERAMIC COATED SPADE BIT


CB25S3



To be used with the Soldron 25W Soldering Iron

BLACK CERAMIC COATED NEEDLE BIT

CB25N3



To be used with the Soldron 25W Soldering Iron

SPADE NICKEL PLATED BIT

BN35S3



To be used with Soldron 35W Soldering Iron

VARITEMP SPADE PREMIUM GRADE LONG LASTING BIT

BP1530S3



To be used with the Soldron Varitemp Soldering Iron.

DELUXE LONG LASTING SPADE BIT


SBS3



To be used with the Soldron 936 / 938 / 878 D/ 740 Station

DELUXE LONG LASTING NEEDLE BIT

SBN3



To be used with the Soldron 936 / 938 / 878 D/ 740 Station

SPADE NICKEL PLATED BIT

BN50S5



To be used with the Soldron 50W Soldering Iron

SPADE NICKEL PLATED LONG LIE BIT

BN75S6



To be used with the Soldron 75W Soldering Iron

SPADE NICKEL PLATED LONG LIFE BIT

BN100S8



To be used with the Soldron 100W Soldering Iron.

IRON PLATED NEEDLE BIT

SBISTN1



To be used with Soldron IST-100 Soldering Station.

BLACK CERAMIC COATED LONG LASTING MICRO SOLDERING IRON BITS


CB10N2



To be used with Soldron Variable Wattage Micro Soldering Station and SMPS Variable Wattage Micro Soldering Station.

DELUXE FINE NEEDLE BIT

SBN1



To be used with Soldron 936/938/878D/740 Stations.
Compatible with SID60A Soldering Soldron.

DE-SOLDERING PUMP

SOLDRON METAL BODY DESOLDERING PUMP

DESOL

The ideal accessory for removing heated solder from a PCB, is our exceptional Soldron Metal Body Desoldering Pump. The high temperature resistant teflon tip is designed to handle the most stressful desoldering job.



Specifications

Body	: Aluminium
Nozzle	: Teflon Tip
Suction Type	: Vacuum
Movement	: Manual Spring Type

JUMBO DESOLDERING PUMP

DESOL-2

Durable plastic housing and plated springs provide excellent corrosion resistance. Precision metal plunger and insulated vacuum pulse remove solder with ease.



Specifications

Length	: 13 in
Length (Straight Wireway)	: 13 in
Tip Material	: Teflon
Actuation Type	: Spring-Loaded Plunger
Tip Outside Diameter	: 0.22 in
Tip Inside Diameter	: 0.125 in
Overall Length	: 13 in

SOLDERING ELEMENTS

25W ELEMENT

EL25A



Specifications

Brand : Soldron
Power Source : Corded Electric
Mounting : 25W Soldering Iron Element
Burner type : Nichrome

About this item

1. Easy to replace with old Soldering Iron heating element
2. Very easy to install

35W ELEMENT

EL35A



Specifications

Brand : Soldron
Power Source : Corded Electric
Mounting : 35W Soldering Iron Element
Burner type : Nichrome

About this item

1. Easy to replace with old Soldering Iron heating element
2. Very easy to install

50W ELEMENT

EL50A



Specifications

Brand : Soldron
Power Source : Corded Electric
Mounting : 50W Soldering Iron Element
Burner type : Nichrome

About this item

1. Easy to replace with old Soldering Iron heating element
2. Very easy to install

75W ELEMENT

EL75A



Specifications

Brand	: Soldron
Power Source	: Corded Electric
Mounting	: 75W Soldering Iron Element
Burner type	: Nichrome

About this item

1. Easy to replace with old Soldering Iron heating element
2. Very easy to install

100W ELEMENT

EL100A



Specifications

Brand	: Soldron
Power Source	: Corded Electric
Mounting	: 100W Soldering Iron Element
Burner type	: Nichrome

About this item

1. Easy to replace with old Soldering Iron heating element
2. Very easy to install

DC POWER SUPPLY



MN-1510D SOLDRON MINI DC POWER SUPPLY 15V/10A

SPECIFICATIONS OF SOLDRON MINI DC POWER SUPPLY 15V/10A

Output Voltage Range	0-15Volts DC
Output Ampere Range	0-10 Amps
Input Voltage	230V AC
Potentiometer	Multi turn
Over current protection	Can be toggled YES or NO
Display	Independent 7 Segment display for Volts and Amperes
GND	Yes
Sockets for Output	Banana type
Body	ABS and Metal

MN-3010D SOLDRON MINI DC POWER SUPPLY 30V/10A

SPECIFICATIONS OF SOLDRON MINI DC POWER SUPPLY 30V/10A

Output Voltage Range	0-30Volts DC
Output Ampere Range	0-10 Amps
Input Voltage	230V AC
Potentiometer	Multi turn
Over current protection	Can be toggled YES or NO
Display	Independent 7 Segment display for Volts and Amperes
GND	Yes
Sockets for Output	Banana type
Body	ABS and Metal



DC POWER SUPPLY



MN-1505D SOLDRON MINI DC POWER SUPPLY 15V/5A

SPECIFICATIONS OF SOLDRON MINI DC POWER SUPPLY 15V/5A

Output Voltage Range	0-15Volts DC
Output Ampere Range	0-5 Amps
Input Voltage	230V AC
Potentiometer	Multi turn
Over current protection	Can be toggled YES or NO
Display	Independent 7 Segment display for Volts and Amperes
GND	Yes
Sockets for Output	Banana type
Body	ABS and Metal

MN-305D SOLDRON MINI DC POWER SUPPLY 30V/5A

SPECIFICATIONS OF SOLDRON MINI DC POWER SUPPLY 30V/5A

Output Voltage Range	0-30Volts DC
Output Ampere Range	0-5 Amps
Input Voltage	230V AC
Potentiometer	Multi turn
Over current protection	Can be toggled YES or NO
Display	Independent 7 Segment display for Volts and Amperes
GND	Yes
Sockets for Output	Banana type
Body	ABS and Metal



MOBILE REPAIRING TOOLS

G-20 / G-21



**TRANSPRANT / SUPER
PURPOSE ADHESIVE**

PRECISION KNIFE



PRECISION CRAFT KNIFE

SS022B



ANTI-STATIC BRUSH

UV559



FLUX PASTE

SS - 109



**PRECISION CUTTER
PLIERS**

RT-14A



**RELIFE RT-14A
PRECISE TWEEZERS**

MINI 0.6



**HARDENED S2
SCREWDRIVER**

13 In 1



**SOLDRON CHIP
REMOVER KIT 13 IN 1**

IR10 PRO



**OCA GLUE
REMOVER TOOLS**

DE-SOLDERING KIT

SOLDERING & DESOLDERING KIT

This Kit Includes.

- 1) Varitemp Variable Wattage Iron with Imported Ceramic Heater Element.
- 2) High Performance Suction Pump.
- 3) 1.1mm Suction Nozzle Bit for Ic's, Transistors, Small Resistor & Capacitors.
- 4) 1.6mm for Power Capacitors, Socket & Wire Wound Resistors.
- 5) Pencil Type PremiumGrade Bit for Soldering.
- 6) Powder Coated Stand with Sponge to Place Iron Safely.
- 7) Specially Formulated Soldering & desoldering Flux.
- 8) Flux Cleaner.
- 9) S.S. Pin for Cleaning Nozzle of Bit.
- 10) Soldering Wire (50g)



SOLDERING & DESOLDERING KIT

This Kit Includes.

- 1). SOLDRON SMPS Micro Soldering & Desoldering Station.
- 2). SOLDRON Pencil Type Premium Grade Bit for Soldering.
- 3). SOLDRON Powder Coated Stand with Sponge to Place Iron Safely.
- 4). SOLDRON Specially Formulated Soldering & Desoldering Flux.
- 5). SOLDRON Flux Cleaner.
- 6). SOLDRON Solder Wire (50 g).
- 7). SOLDRON High Performance Premium Desoldering Pump.



ACCESSORIES

SSIT



**SOLDRON SOLDERING
IRON THERMOMETER**

MAT- 55/38



**SOLDRON ESD SAFE
WORKING BIG MAT
WITH MAGNET**

SIMAT2820



**SOLDERING MAT
(BLUE & BLACK)**

ASSIST SET



**SOLDERING 6 IN 1
SOLDER ASSIST SET**

TWZC



**TWEEZER AND
CUTTER POUCH SET**

NZL



**HOT AIR BLOWER'S
NOZZLES**

FA400



**SOLDRON FUME
EXTRACTOR**

FC-10ML



**SOLDRON SOLDERING
FLUX (10ML)**

BARREL



**SOLDERING STATION
IRON'S BARREL SET**

SISDX



**DELUXE SOLDERING
IRON STAND**

CRADLE



**878/740 HOT AIR BLOWER
CRADLE/STAND**

PUMP NOZZEL



**DESOLDERING PUMP'S
SPARE NOZZEL**

ACCESSORIES

SPONGE ROUND SHAPE



**SPONGE ROUND
SHAPE**

SSS



SPONGE SQUARE

SWD



**SOLDRON SOLDER
WIRE DISPENSER**

SOLDER WIRE



**PREMIUM SOLDER WIRE
50 & 100 GMS**

STPH



**SOLDRON TRIPOD
PCB HOLDER**

TIPC



**SOLDRON BIT-TIP
TINNER AND CLEANER**

FC-200ML



**SOLDRON SOLDERING
FLUX (200ML)**

**QUICKFIX SOLDERING
PASTE 50GM**



**QUICKFIX SOLDERING
PASTE FLUX 50GM**

BIG CROCODILE CLIP



**BIG CROCODILE CLIP
PACK OF 10 (5 PAIR)**

REPAIR TOOLS SET



**5 IN 1 MULTIFUNCTION
SCREWDRIVER KIT**

MT-02DX



**MULTITEC MT-02DX
SELF ADJUSTING
CUTTER/STRIPPER**

UTP - 41



**UNIVOLT UTP-41 300W
SOLDER POT 100MM**



Since 1953

BOMBAY INSULATED CABLES & WIRES CO.



www.soldermall.com

Established in 1953, Bombay Insulated Cables & Wires Co. is a trading firm which is a leading authorized distributor and dealer for SOLDRON Brand of Soldering Irons and Accessories all over India and abroad to fulfill industrial needs. Their fully owned subsidiary Soldermall is successfully retailing Soldron and other soldering related products online from www.soldermall.com and has earned excellent goodwill in the online retail sector in India. BICW is also into distribution and retail of some other well-known brands like Axelon Cables and Wires. They focus on supplying the highest quality of products and excellent personalized service.

Registered Address:

74, Horniman Chambers, S.A. Brelvi Road,
Fort, Mumbai - 400 001.

Correspondence Address.

157/ A2 Shah & Nahar Industrial Estate,
S. J. Marg, Lower Parel (W), Mumbai - 400 013.

🌐 Website : www.soldermall.com

✉ Email : sales@bicw.co.in

☎ Customer Care No.: (022) 48973337